


1 DOOR TYPE ELEVATIONS
1/4" = 1'-0"
NOTE:
REFER TO FLOOR PLAN FOR DOOR SWING DIRECTION

2 DOOR CLEARANCE DETAIL (TYP.)
1/4" = 1'-0"



DOOR #	LOCATION	TYPE	SIZE		DOOR						FRAME			SEE SHEET DETAILS A-603			REMARKS	
			WIDTH	HEIGHT	THICKNESS	MATERIAL	GLAZING	FINISH	RATING	HARDWARE SET	STOP TYPE	MATERIAL	FINISH	RATING	HEAD	JAMB		SILL
101A	ELECTION ROOM	A	(2)-3'-0"	7'-0"	BY MNF.	BY MNF.	1" INSULATED GLASS	DARK BRONZE	N/A	1	CLOSER	BY MNF.	BY MNF.	NO	H1	J1	S1, S2	
101B	ELECTION ROOM	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	PAINT WALL COLOR	N/A	4	HINGE STOP	HOLLOW METAL	PAINTED	NO				(6)
102A	VESTIBULE	A	(2)-3'-0"	7'-0"	BY MNF.	BY MNF.	1" INSULATED GLASS	DARK BRONZE	N/A	1	CLOSER	BY MNF.	BY MNF.	NO	H1	J1	S1, S2	
103A	PUBLIC OBSERVATION ROOM	D	3'-0"	7'-0"	1 3/4"	SOLID CORE	1" INSULATED GLASS	STAIN AND SEAL	N/A	2	CLOSER	HOLLOW METAL	PAINTED	NO	H4	J1	S1, S2	
104A	CORRIDOR	E	3'-0"	7'-0"	1 3/4"	SOLID CORE	1" INSULATED GLASS	STAIN AND SEAL	N/A	1	CLOSER	HOLLOW METAL	PAINTED	NO	H4	J1	S1, S2	
105A	FRONT OFFICE	EXISTING	3'-0"	7'-0"						6				NO				(2)
106A	STORAGE	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	4	HINGE STOP	HOLLOW METAL	PAINTED	NO	H3	J3	S4	
107A	CORRIDOR	G	3'-0"	7'-0"										NO				(3)
108A	PUBLIC OBSERVATION ROOM	D	3'-0"	7'-0"	1 3/4"	SOLID CORE	1" INSULATED GLASS	STAIN AND SEAL	N/A	2	CLOSER	HOLLOW METAL	PAINTED	NO	H4	J3, J4	S4, S5	
109A	ABSENTEE ROOM	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	4	CLOSER	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	(1)
110A	MEN RESTROOM	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	5	CLOSER	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	
111A	WOMEN RESTROOM	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	5	CLOSER	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	
112A	CORRIDOR	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	2	CLOSER	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	
112B	CORRIDOR	G	4'-0"	7'-0"										NO	H5	J5		(3)
112C	CORRIDOR	C	4'-0"	7'-0"	BY MNF.	HOLLOW METAL	NO	STAIN AND SEAL	N/A	1	CLOSER	BY MNF.	BY MNF.	NO	H3.1	J3.1	S4, S5	(1)
113A	CORRIDOR	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	4		HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	(1)
114A	CORRIDOR	EXISTING	3'-0"	7'-0"						6				NO				(2)
115A	ELECTRICAL ROOM	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	4	HINGE STOP	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	
117A	STAGING ROOM	F	4'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	3	WALL STOP	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	(1)
117B	STAGING ROOM	EXISTING	3'-0"	7'-0"						6				NO				(2)
117C	STAGING ROOM	EXISTING	3'-0"	7'-0"						6				NO				(2)
118A	HVAC CLOSET	EXISTING	3'-0"	7'-0"						6				NO				(2)
119A	OFFICE	EXISTING	3'-0"	7'-0"						6				NO				(1, 2)
119B	OFFICE	EXISTING	3'-0"	7'-0"						6	CLOSER			NO				(2)
120A	EMS ROOM	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	4		HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	(1)
121A	CORRIDOR	B	3'-0"	7'-0"	BY MNF.	BY MNF.	1" INSULATED GLASS	STAIN AND SEAL	N/A	1	CLOSER	BY MNF.	BY MNF.	NO	H1	J1	S1	(1)
121B	CORRIDOR	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	4	CLOSER	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	(1)
122A	MEN RESTROOM	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	5	CLOSER	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	
123A	WOMEN RESTROOM	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	5	CLOSER	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	
124A	OFFICE	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	4	CLOSER	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	
125A	LOBBY	A	(2)-3'-0"	7'-0"	BY MNF.	BY MNF.	1" INSULATED GLASS	DARK BRONZE	N/A	1	CLOSER	BY MNF.	BY MNF.	NO	H1	J1	S1, S2	
126A	STORAGE	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	4	HINGE STOP	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	
127A	FRONT OFFICE	EXISTING	3'-0"	7'-0"						6				NO	H3	J3	S4, S5	(2)
127B	FRONT OFFICE	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	4	HINGE STOP	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	(1)
128A	CORRIDOR	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	2	CLOSER	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	(5)
129A	SERVER	F	3'-0"	7'-0"	1 3/4"	SOLID CORE	NO	STAIN AND SEAL	N/A	4	HINGE STOP	HOLLOW METAL	PAINTED	NO	H3	J3	S4, S5	
130A	OFFICE	EXISTING	3'-0"	7'-0"						6				NO				(2)
DOOR DELETED																		

- NOTES**
- DOOR WITH CONTROLLED ACCESS - G.C. TO COORDINATE WITH OWNER AND OWNER'S SECURITY AND LOW VOLTAGE VENDOR. COORDINATE WITH PROJECT ELECTRICAL ENGINEER AS NEEDED.
 - EXISTING DOOR. G.C. REPAIR ALL EXISTING DOORS TO REMAIN AS NECESSARY. EXISTING DOOR HARDWARE TO REMAIN UNLESS CONTROLLED ACCESS IS NOTED FOR THE DOOR. COORDINATE ALL REQUIREMENTS FOR HARDWARE WITH CONTROLLED ACCESS AND PROVIDE NEW HARDWARE AS REQUIRED.
 - G.C. COORDINATE CASED OPENING WITH DEMOLITION AND PREPARE NEW OPENING FOR HOLLOW METAL FRAME.
 - DELETED
 - G.C. PROVIDE "NO EXIT" SIGNAGE ON PULL SIDE OF THE DOOR
 - ACCESS DOOR TO EXISTING WATER SERVICE

- NOTES**
- GENERAL:**
- DOOR SHALL BE INSTALLED A MIN OF 3" FROM ADJACENT WALL ON HINGE SIDE (UNLESS DIMENSIONED OTHERWISE)
 - INSULATION SHALL BE USED TO FILL VOIDS AT DOOR PERIMETER.
 - ANCHOR DOOR THRU HINGES AT TOP HOLE OF HINGE. SHIM AND PLUMB UNITS AS REQUIRED.
 - SET UNITS IN CONTINUOUS SEALANT
 - ANCHOR DOOR TO OPENING AT PREDRILLED HOLES. OPENING MUST BE LEVEL PRIOR TO INSTALLING UNIT.
 - SAFETY GLAZING IBC 2046.3-6. EX. 10: GLAZING ADJACENT TO STAIRWAYS, LANDINGS AND RAMP WITHIN 36" HORIZONTALLY OF A WALKING SURFACE, WHERE THE EXPOSED SURFACE OF THE GLASS IS LESS THAN 60" ABOVE THE PLANE OF THE ADJACENT WALKING SURFACE.
- HARDWARE:**
- HARDWARE SHALL BE PER 2010 A.D.A. STANDARDS.
 - ALL HARDWARE SHALL BE LEVER-OPERATED MECHANISM, PUSH-TYPE MECHANISM OR U-SHAPED HANDLES. HARDWARE SHALL BE MOUNTED 40" ABOVE FINISHED FLOOR PER INDUSTRY STANDARDS. G.C. COORDINATE ANY DEVIATIONS WITH AN ARCHITECT.
 - ALL KEYED ENTRIES SHALL BE MASTER KEYED. WHERE PANIC HARDWARE IS REQUIRED ON FIRE RATED DOORS, SUCH HARDWARE SHALL BE LISTED AS "FIRE EXIT HARDWARE"

TYPE	HARDWARE SET
1	PANIC PUSH BAR w/ KEYED ENTRY + THUMB TURN
2	PASSAGE
3	KEYED LOCK OFFICE FUNCTION
4	KEYED STOREROOM
5	PRIVACY
6	EXISTING HARDWARE. G.C. COORDINATE WITH OWNER IF TO BE REMOVED. FOR BID PURPOSE PROVIDE ALLOWANCE FOR NEW HARDWARE. - COORDINATE DOOR HARDWARE FOR DOOR #119A TO ALLOW FOR CONTROLLED ACCESS.

PRINT RECORD

#	DESCRIPTION	DATE	BY
1	REVISION PER CLIENT	JUNE 21, 2021	

FAYETTE COUNTY ELECTIONS OFFICE
REMODEL

175 JOHNSON AVENUE
FAYETTEVILLE, 30214 GEORGIA
PROJECT #3142



FINAL DRAWING
FOR REVIEW PURPOSES ONLY
Release Date: May 25, 2021

DOOR
SCHEDULE AND
ELEVATIONS